

Rotule GE SIZPL25-S-DURBAL - SIZPL25-S-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/ge/sizpl25-s-durbal>

SIZPL25-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches

order number

right hand thread	left hand thread	d	G	B	measurement (mm)	d ₂	d ₃	d ₄
SIZPL 25 S		25,40	5/8 - 12	34,93	25,40	69,85	37,72	44,45

type

type	inches	l ₁ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SIZP / SIZPL 25 S	1"	53,98	38,10	104,78	14	101,0	1,000

Diagram: Technical drawing showing cross-sections of the rod end with dimensions B, C₁, d₂, d₃, d₄, G, W, d, and d₁.

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple

Rod end body: surface zinc plated

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060467843
Diam. intérieur	25.4 mm
Diam. extérieur	69.85 mm
Epaisseur	34.93 mm
Type	GE
Poids	1000 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE