

Rotule SI

SIZJL6-DURBAL - SIZJL6-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/sizj6-durbal>

SIZJL6



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / steel.
Size: 9 with grease nipple can be mounted upon request.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required

order number	right hand thread	left hand thread	measurement [mm]					
SIZJL 6	6,35	9,53	6,35	19,05	1/4 - 28	9,15	11,91	

type	inches	h ₁ min	measurement [mm]		α	load rating	weight
			W	h	[°]	C ₀ [kN]	[g]
SIZJ / SIZJL 6	1 / 4 "	15,88	9,53	33,32	13,5	9,6	0,023

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952496702
Diam. intérieur	6.35 mm
Diam. extérieur	19.05 mm
Epaisseur	9.53 mm
Type	SI
Poids	23 g
Filetage	Filetage à gauche
Lubrification	sans
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE