

## Rotule SI SI25-ES-2RS-DURBAL - SI25-ES-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/si25-es-2rs-durbal>

### SI25-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.

**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 25 ES (-2RS)			25	M 24 x 2	20	17,0	64	33,5	42

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	α [°]		
SI / SIH 25 ES (-2RS)	48	36	94	7	83,0	0,64

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497198
Diam. intérieur	25 mm
Diam. extérieur	64 mm
Epaisseur	20 mm
Type	SI
Poids	640 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE