

Rotule SI SI30-ES-DURBAL - SI30-ES-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/si30-es-durbal>

SI30-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SI 30 ES		30	M 30 x 2

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_1 min	W	h			
SI / SI30 ES	56	41	110	6	110,0	0,93

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497235
Diam. intérieur	30 mm
Diam. extérieur	73 mm
Epaisseur	22 mm
Type	SI
Poids	930 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE