

Rotule SI

SI35-ES-2RS-DURBAL - SI35-ES-2RS-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/si35-es-2rs-durbal

SI35-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number	right hand thread	left hand thread	d	G	measurement [mm]				
					B	C1	d2	d3	d4
SI 35 ES (-2RS)			35	M 36 x 3	25	21,0	82	47,0	58

type	measurement [mm]				load rating C_0 [kN]	weight [kg]
	l_1 min	W	h	α [°]		
SI / SI1 35 ES (-2RS)	60	50	125	6	146,0	1,3

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497358
Diam. intérieur	35 mm
Diam. intérieur	1.378" inch
Diam. extérieur	82 mm
Diam. extérieur	3.228" inch
Epaisseur	25 mm
Epaisseur	0.984" inch
Type	SI
Poids	1300 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE