

Rotule SI SI40-ES-DURBAL - SI40-ES-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/si40-es-durbal>

SI40-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 40 ES			40	M 39 x 3	28	23,0	92	52,0	65

type	l ₁ min	W	h	α	load rating C ₀ [kN]	weight [kg]
SI / SII 40 ES	65	55	142	7	180,0	2,0

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497396
Diam. intérieur	40 mm
Diam. extérieur	92 mm
Épaisseur	28 mm
Type	SI
Poids	2000 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE