

Rotule SI SI50-ES-DURBAL - SI50-ES-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/si50-es-durbal>

SI50-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 50 ES		50	M 45 x 3	35	30,0	112	62,0	75

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SI L 50 ES	68	65	160	6	290,0	3,5

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497556
Diam. intérieur	50 mm
Diam. extérieur	112 mm
Epaisseur	35 mm
Type	SI
Poids	3500 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE