

# Rotule SI

## SIL50-ES-DURBAL - SIL50-ES-DURBAL

https://www.123roulement.com/roulement-palier/rotule/si/sil50-es-durbal

### SIL50-ES



**female thread; lubrication required, according to DIN ISO 12240-4; serie E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSL...ES-2RS with additional seals also available.

**Rod end body:** surface zinc plated

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

order number	right hand thread	left hand thread	measurement [mm]						
SIL 50 ES			d	G	B	C1	d2	d3	d4
			50	M 45 x 3	35	30,0	112	62,0	75

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	W	h	α [°]		
SI / SIL 50 ES	68	65	160	6	290,0	3,5

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497587
Diam. intérieur	50 mm
Diam. extérieur	112 mm
Épaisseur	35 mm
Type	SI
Poids	3500 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE