

Rotule SI SI60-ES-DURBAL - SI60-ES-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/si60-es-durbal>

SI60-ES



female thread; lubrication required, according to DIN ISO 12240-4; serie E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSL...ES-2RS with additional seals also available.

Rod end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number	right hand thread	left hand thread	d	G	measurement (mm)				d2	d3	d4
SI 60 ES			60	M 52 x 3	44	38,0	135	70,0	88		

type	l1 min	measurement [mm]			alpha [°]	load rating C0 [kN]	weight [kg]
SI / SIL 60 ES	70	75	175	6	450,0	5,5	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497662
Diam. intérieur	60 mm
Diam. extérieur	135 mm
Epaisseur	44 mm
Type	SI
Poids	5500 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE