

## Rotule SA SA10-E-DURBAL - SA10-E-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/sa10-e-durbal>

### SA10-E



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 10 E		10	M 10	9	7,0	29
type	l <sub>1</sub> min	l <sub>2</sub>	h	n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
SA / SA 10 E	26	15	48	12	17,6	0,051

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952497945
Diam. intérieur	10 mm
Diam. extérieur	29 mm
Epaisseur	9 mm
Type	SA
Poids	51 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE