

## Rotule SA SA20-ES-DURBAL - SA20-ES-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/sa20-es-durbal>

### SA20-ES



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number	measurement [mm]						
	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 20 ES			20	M 20 x 1,5	16	13,0	53

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 20 ES	43	27	78		9	60,0	0,310

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952498188
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	53 mm
Diam. extérieur	2.087" inch
Epaisseur	16 mm
Epaisseur	0.63" inch
Type	SA
Poids	310 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE