

## Rotule SA SA40-ES-2RS-DURBAL - SA40-ES-2RS-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/sa40-es-2rs-durbal>

### SA40-ES-2RS



**male thread:**  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

**rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SA 40 ES (-2RS)		40	M 39 x 3	28	23,0	92

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 40 ES (-2RS)	86	46	150		7	180,0	1,800

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952498508
Diam. intérieur	40 mm
Diam. extérieur	92 mm
Epaisseur	28 mm
Type	SA
Poids	1800 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE