

## Rotule SA SAL80-ES-DURBAL - SAL80-ES-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/sal80-es-durbal>

### SAL80-ES



**male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.

**rod end body:  
surface zinc plated**

**Sliding combination:  
steel / steel**

**Inner ring:  
bearing steel, hardened, ground and phosphated**

**Outer ring:  
bearing steel, hardened, ground and phosphated**

**Lubrication:  
lubrication is necessary**

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
	<b>SAL 80 ES</b>	80	M 64 x 4	55	47,0	180

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 80 ES	140	90	270		6	750,0	12,000

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952498911
Diam. intérieur	80 mm
Diam. extérieur	180 mm
Epaisseur	55 mm
Type	SA
Poids	12000 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE