

## Rotule TAPR GIHO-KL-12DO-DURBAL - GIHO-KL-12DO-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/tapr/giho-kl-12do-durbal>

### GIHO-KL-12DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
			d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>
GIHO-KL 12 DO*			12	15,0	35	M 10 x 1,25	17	40	10	8	13

type	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
GIHO-K / GIHO-KL 12 DO*	42	15	59,5	16	11	17,0	0,12

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500614
Diam. intérieur	12 mm
Diam. extérieur	35 mm
Epaisseur	8 mm
Type	TAPR
Poids	120 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE