

Rotule TAPR GIHO-K-16DO-DURBAL - GIHO-K-16DO-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/tapr/giho-k-16do-durbal>

GIHO-K-16DO

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₃	d ₄	B	C ₁	C ₂	
GIHO-K 16 DO*		16	20,7	45	M 12 x 1,25	21	45	14	11	13	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 16 DO	48	17	70,5	20	10	28,5	0,22

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500652
Diam. intérieur	16 mm
Diam. intérieur	0.63" inch
Diam. extérieur	45 mm
Diam. extérieur	1.772" inch
Epaisseur	11 mm
Epaisseur	0.433" inch
Type	TAPR
Poids	220 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE