

Rotule TAPR GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/tapr/giho-kl-40do-durbal>

GIHO-KL-40DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | | | |
|---------------|-------------------|------------------|------------------|----------------|----------------|----------|----------------|----------------|----|----------------|----------------|
| GIHO-KL 40 DO | | | d | d ₁ | d ₂ | G | d ₄ | d ₅ | B | C ₁ | C ₂ |
| | | | 40 | 45,0 | 100 | M 27 x 2 | 45 | 90 | 28 | 23 | 23 |

| type | h ₁ | l ₁ | l ₂ | l ₃ | α [°] | load rating C ₀ [kN] | weight [kg] |
|------------------------|----------------|----------------|----------------|----------------|-------|---------------------------------|-------------|
| GIHO-K / GIHO-KL 40 DO | 105 | 37 | 155,0 | 45 | 7 | 156,0 | 2,16 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|-------------------|
| Marque | DURBAL |
| N° Ean13 | 3663952500805 |
| Diam. intérieur | 40 mm |
| Diam. extérieur | 100 mm |
| Epaisseur | 23 mm |
| Type | TAPR |
| Poids | 2160 g |
| Filetage | Filetage à gauche |
| Lubrification | avec |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE