

Rotule TAPR GIHO-KL-80DO-DURBAL - GIHO-KL-80DO-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/tapr/giho-kl-80do-durbal>

GIHO-KL-80DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]								
			d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
GIHO-KL 80 DO			80	89,4	205	M 48 x 2	90	156	55	47	47

type	h ₁	l ₁	l ₂	l ₃	α [°]	load rating C ₀ [kN]	weight [kg]
GIHO-K / GIHO-KL 80 DO	185	64	287,5	82	6	585,0	15,00

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952500935
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	205 mm
Diam. extérieur	8.071" inch
Epaisseur	47 mm
Epaisseur	1.85" inch
Type	TAPR
Poids	15000 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE