

Rotule GEG GE25-LO-DURBAL - GE25-LO-DURBAL


<https://www.123roulement.com/roulement-palier/rotule/geg/ge25-lo-durbal>

GE25-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

order number	measurement [mm]				
GE 25 LO	d	B	C	d ₁ min	D
	25	25	16	30,0	42

type	measurement [mm]		d ₂	r ₁	load rating C ₁₀ [N]	weight [kg]
	r ₂₅ min	r ₂₅ min				
GE 25 LO	0,6	0,6	35,5	4	240	0,120

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506401
Diam. intérieur	25 mm
Diam. extérieur	42 mm
Epaisseur	16 mm
Type	GEG
Poids	120 g
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE