


Rotule GEG
GE50-LO-DURBAL - GE50-LO-DURBAL
<https://www.123roulement.com/roulement-palier/rotule/geg/ge50-lo-durbal>

GE50-LO



spherical plain bearing:
similar to
DIN ISO 12240-1,
series W

inner ring:
bearing steel, hardened, ground and
phosphated, with cylindric extension on
both sides

outer ring:
bearing steel, hardened, ground and
phosphated, single split in axial direction

Lubrication:
lubrication required

Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

Sliding combination:
steel / steel

order number	measurement [mm]				
	d	B	C	d ₂ min	D
GE 50 LO	50	50	28	57.0	75

type	measurement [mm]				load rating C ₁₀ [N]	weight [kg]
	r ₁ min	r ₂ min	d ₁	α ₁ [°]		
GE 50 LO	0.6	1.0	66.0	4	780	0.560

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506500
Diam. intérieur	50 mm
Diam. extérieur	75 mm
Epaisseur	28 mm
Type	-
Poids	560 g
Lubrification	-
Conditionnement	-
Norme	-

contact@123roulement.com
03 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE