

Rotule GEG GE60-LO-DURBAL - GE60-LO-DURBAL


<https://www.123roulement.com/roulement-palier/rotule/geg/ge60-lo-durbal>

GE60-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

order number	measurement [mm]				
GE 60 LO	d	B	C	d ₂ min	D
	60	60	36	68,0	90

type	measurement [mm]		d ₁	α [°]	load rating C ₁₀ [N]	weight [kg]
	r ₁₅ min	r ₂₅ min				
GE 60 LO	1,0	1,0	80,0	4	1220	1,150

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506517
Diam. intérieur	60 mm
Diam. intérieur	2.362" inch
Diam. extérieur	90 mm
Diam. extérieur	3.543" inch
Epaisseur	36 mm
Epaisseur	1.417" inch
Type	GEG
Poids	1150 g
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE