

Rotule GEG GE70-LO-DURBAL - GE70-LO-DURBAL


<https://www.123roulement.com/roulement-palier/rotule/geg/ge70-lo-durbal>

GE70-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring:
bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication:
lubrication required

| order number | measurement [mm] | | | | |
|--------------|------------------|----|----|--------------------|-----|
| | d | B | C | d ₂ min | D |
| GE 70 LO | 70 | 70 | 40 | 79.0 | 105 |

| type | measurement [mm] | | d ₁ | α [°] | load rating C ₁₀ [kN] | weight [kg] |
|----------|---------------------|---------------------|----------------|-------|----------------------------------|-------------|
| | r ₁₅ min | r ₂₅ min | | | | |
| GE 70 LO | 1.0 | 1.0 | 92.0 | 4 | 1560 | 1.700 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | DURBAL |
| N° Ean13 | 3663952506555 |
| Diam. intérieur | 70 mm |
| Diam. extérieur | 105 mm |
| Epaisseur | 40 mm |
| Type | - |
| Poids | 1700 g |
| Lubrification | - |
| Conditionnement | - |
| Norme | - |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE