

Rotule SA BRTM20-00-502-DURBAL - BRTM20-00-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/brtm20-00-502-durbal>

BRTM20-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, trial of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]						
type	type hard chrome, left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	b ₁	b ₂
BRTM 20 -00	-502	20	M 20 x 1,5	24,5	50	25	18	
measurements [mm]		weight		rotational speed limit		basic load rating		
type	h	l	b ₃	α	[°]	[kg]	n _{max} [rpm]	d _m [N]
BRTM 20	78	47	28	7,0		0,340	825	17000 11700

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952506777
Diam. intérieur	20 mm
Diam. extérieur	50 mm
Epaisseur	25 mm
Type	SA
Poids	340 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE