

Rotule GE

BRTF20-00-501-DURBAL - BRTF20-00-501-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/ge/brtf20-00-501-durbal>

BRTF20-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]																				
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	h ₁	h ₂	h	l ₁	l ₂	l ₃	SW	α [°]	weight [kg]	rotational speed limit n _{max} [min ⁻¹]	basic load rating C [N]	stat. rating C ₀ [N]	
BRTF 20 -00	-501		20	27,5	M 20 x 1,5	24,5	50	34	25	18												
BRTF 20			77	33	10,0	26	30	7,0	0,361	825	17000	11700										

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3616060468185
Diam. intérieur	20 mm
Diam. extérieur	50 mm
Epaisseur	25 mm
Type	GE
Poids	361 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE