


Rotule SI

PF20-00-502-DURBAL - PF20-00-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/pf20-00-502-durbal>

PF20-00-502



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

female thread;
long-term lubrication, low maintenance, shields



order number		measurements [mm]										
type	type load shield	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃		
PF 20 -00	-502	20	22	M 16	24,0	48	20,5	15				
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		stat.		
type	h	l ₁	l ₂	r	SW	α	γ	Y	Y ₀	n _{max} [rpm]	C	C ₀ [N]
PF 20	65	32	22,0	20	19	6,5	0,223	2,34	2,45	850	6105	2955

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507415
Diam. intérieur	20 mm
Diam. extérieur	48 mm
Epaisseur	20.5 mm
Type	SI
Poids	223 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE