

Rotule SA PM05-00-501-DURBAL - PM05-00-501-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/pm05-00-501-durbal>

PM05-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating				
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	dyn.	stat.	C ₀			
PM 05 -00	-501	S	M 8x1	7,5	19	12	12	12	8					
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	Y	γ ₀	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 05	39,5	13	57	1,5	2,5	7,0	0,037			1,51	1,58	1350	1610	480

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507422
Diam. intérieur	5 mm
Diam. extérieur	19 mm
Epaisseur	12 mm
Type	SA
Poids	37 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE