

Rotule SA PM05-01-502-DURBAL - PM05-01-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/pm05-01-502-durbal>

PM05-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		weight		rotational speed limit		basic load rating				
type	specification	d ₁	d ₂	d ₄	d ₅	Y	n _{max} [min ⁻¹]	C	C ₀ [N]			
PM 05 -01	-502	S	M 8 x 1	7,5	19	12	12	12	8			
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	α' [°]			
PM 05	16	13	33,5	1,5	2,5	7,0	0,033	1,51	1,58	1350	1610	480

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507446
Diam. intérieur	5 mm
Diam. extérieur	19 mm
Epaisseur	12 mm
Type	SA
Poids	33 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE