

Rotule SA PM06-02-501-DURBAL - PM06-02-501-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/pm06-02-501-durbal>

PM06-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating				
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	Y	C			
PM 06 -02	-501	6	M 10 x 1	8,5	24	14	14	10						
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	weight [kg]	Y	Y _c	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 06	19	17	40,5	1,5	2,5	10,5	0,057		1,28	1,34	1300	2445	765	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507491
Diam. intérieur	6 mm
Diam. intérieur	0.236" inch
Diam. extérieur	24 mm
Diam. extérieur	0.945" inch
Epaisseur	14 mm
Epaisseur	0.551" inch
Type	SA
Poids	57 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE