

Rotule SA

PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/pm15-02-501-durbal>

PM15-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		weight		rotational speed limit		basic load rating	
type	approx. weight [kg]	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂
PM 15 -02 -501		15	M 20 x 1.5	18.5	42	26	20	14	
measurements [mm]		weight		rotational speed limit		basic load rating			
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	
PM 15	36	30	73.5	3.0	2.5	6.5	0.273		
		weight		rotational speed limit		basic load rating			
		[kg]		Y		C		C ₀	
				2.07	2.17	975	5485	3270	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507651
Diam. intérieur	15 mm
Diam. extérieur	42 mm
Epaisseur	20 mm
Type	SA
Poids	273 g
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE