

Rotule SA PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/pm17-01-502-durbal>

PM17-01-502



male thread:
long-term
lubrication,
low maintenance,
shields

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminium-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]		weight		rotational speed limit		basic load rating	
type	specification	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16	
measurements [mm]		weight		rotational speed limit		basic load rating			
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'
PM 17	36	36	78,5	3,5	2,5	7,0	0,354	2,35	2,46
		weight		rotational speed limit		basic load rating			
		[kg]		n _{max} [min ⁻¹]		C [N]		C ₀ [N]	
		0,354		2,35 2,46		875 5575		2680	

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952507682
Diam. intérieur	17 mm
Diam. extérieur	48 mm
Epaisseur	22 mm
Type	SA
Poids	354 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE