


Rotule SI

BRF1-2-00-502-DURBAL - BRF1-2-00-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/brf1-2-00-502-durbal>

BRF1/2-00-502 

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1 1/2)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]										
type	right hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b2	b3	
BRF 1/2 -00	-502	500	.748	5000-20 UNF	574	1.311	.874	.624	.472			
measurements [inches]		weight		calculation factors		rotational speed limit		basic load rating		stat.		
type	h	l	l1	l2	SW	α [°]	Y	Trmax [mm]	C [N]	C0 [N]	stat. [N]	
BRF 1/2	2.145	1.102	.279	.649	.757	7.5	0,127	1,74	1,82	1125	4850	1850

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510156
Diam. intérieur	12.7 mm
Diam. intérieur	1/2" inch
Diam. extérieur	33.3 mm
Diam. extérieur	1.311" inch
Epaisseur	15.85 mm
Epaisseur	0.624" inch
Type	SI
Poids	127 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE