


Rotule SI

BRF1-1-00-502-DURBAL - BRF1-1-00-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/si/brf1-1-00-502-durbal>

BRF1/1-00-502 

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1 1/4)


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]									
type	right hand thread	d1	d2	d3	d4	d5	d6	d7	b1	b2	b3
BRF 1/1 -00	-502	1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866		
measurements [inches]		weight		rotational speed limit		basic load rating					
type	h	l	l1	l2	SW	α [°]	weight [kg]	calculation factors Y %	rotational speed limit [rpm]	basic load rating dyn. C [N]	basic load rating stat. C0 [N]
BRF 1/1	3.720	1.653	.236	1.279	1.181	5.0	0.570	2.02 2.12	600	11030	5680

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510200
Diam. intérieur	25.4 mm
Diam. extérieur	63.98 mm
Épaisseur	30.99 mm
Type	SI
Poids	570 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE