

# Rotule SA BRM1-4-00-502-DURBAL - BRM1-4-00-502-DURBAL

<https://www.123roulement.com/roulement-palier/rotule/sa/brm1-4-00-502-durbal>

## BRM1/4-00-502



**male thread:**  
long-term  
lubrication,  
low maintenance,  
shields,  
dimensions in inches

**DURBAL® heavy-duty rod ends  
with integral self-aligning  
ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened,  
superfinished

**lubrication:**  
aluminum-complex soap grease,  
temperature range -45 °C to +120 °C,  
approval according to USDA H1

**lubrication fitting:**  
DIN 3425 D1/A (sizes 1/4 and 3/8)  
DIN 71 412 H1 (sizes 1/2 and 1/1)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [inches]								
type	right hand thread, left hand thread	d <sub>1</sub>	d <sub>2</sub> class 2	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>
BRM 1/4 -00	-502	.250	2500-28 UNF	.356	.787	.354	.265			
measurements [inches]		weight		calculation factors		rotational speed limit		basic load rating		stat.
type	h	l	l <sub>3</sub>	α [°]	Y	v <sub>0</sub>	rpm [min]	C [N]	C <sub>0</sub> [N]	C <sub>0</sub> [N]
BRM 1/4	1.437	.866	.551	8.0	0,022	2,09	2,19	1350	2670	645

## CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952510255
Diam. intérieur	6.35 mm
Diam. extérieur	19.99 mm
Epaisseur	8.99 mm
Type	SA
Poids	22 g
Filetage	Filetage à gauche
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE