

## Roulement autre


# AXNBT2068-NADELLA - AXNBT2068-NADELLA

https://www.123roulement.com/roulement-palier/roulement-autre/axnbt2068-nadella

**Precision combined bearings,  
with adjustable axial preload**



AXNBT and ARNBT  
series



- 1) 6% of dynamic axial load
- 2) with axial load equal to preload
- 3) rigidity of a single thrust bearing with load equal to preload
- 4) hexagon socket shallow head cap screw DIN 91

Shaft Ø mm	Designation			d mm	D mm	F <sub>ax</sub> mm	D <sub>A</sub> mm	D <sub>M</sub> mm	B mm	C mm	B <sub>2</sub> mm	r mm	r <sub>1</sub> mm	Screw TCE II class 12.9 N° viti	Mounting			Torque Nm
	AXNBT	ARNBT series 1	ARNBT series 2												E mm	e mm	9	
20	20 68			20	68	25	42	32.5	40	16	12	0.85	0.85	6x20	8	53	9	10

Load Ratings kN				Speed rating min <sup>-1</sup>	Preload <sup>1)</sup> N	Rotation <sup>2)</sup> torque Nmm	Rigidity K to N/mm	Weight kg	Designation
radial	axial		Stat. Co						
Dyn. C	Stat. Co	Dyn. C	Stat. Co	7 500	820	160	1 480	0.521	AXNBT 20 68
18.9	28.8	13.5	50.0						

## CARACTÉRISTIQUES PRODUIT

Marque	NADELLA
N° Ean13	3616060472649
Diam. intérieur	20 mm
Diam. intérieur	0.787" inch
Diam. extérieur	42 mm
Diam. extérieur	1.654" inch
Epaisseur	40 mm
Epaisseur	1.575" inch
Poids	521 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE