




Douille à aiguilles TJ7215-RBC - TJ7215-RBC

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/tj7215-rbc>

Heavy Duty TJ TandemRoller® Bearings 

TJ TandemRoller® Bearing

BEARING PART NUMBER 1)	Fw Inside Diameter			D Outside Diameter		B Width	r _s Housing Fillet	Housing Shoulder Dia.	Dynamic Capacity C (lbs.)	Static Capacity C ₀ (lbs.)
	Nominal	Min.	Max.	Max.	Min.	+0.000 -0.005	Max	+/- 1.84"		
TJ 7215	1 1/8	1.1259	1.1268	1.6250	1.6245	1.250	.040	1.3/8	10,600	20,400

Limit Scaled (rpm)	Recommended Shaft Diameter				Recommended Housing Bore				BEARING PART NUMBER 1)		
	ISO H5, use with +F Slip Fit	ISO H6, use with N7 Tight Fit	ISO H7, use with N7 Tight Fit	ISO H8, use with N7 Tight Fit	Slip Fit ISO H7	Press Fit ISO N7	Press Fit ISO N7	Press Fit ISO N7			
	Max.	Min.	Max.	Min.	Min.	Max.	Mean Fit	Min.	Max.	Mean Fit	
10,500	1.1290	1.1245	1.1242	1.1237	1.6250	1.6280	.0007L	1.6237	1.6247	.0006T	TJ 7215

All dimensions in inches.
1) Prefix DTJ denotes a double row bearing.

CARACTÉRISTIQUES PRODUIT

Marque	RBC
N° Ean13	3663952533506
Diam. intérieur	28.575 mm
Diam. extérieur	41.275 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE