


Roulement à bille simple rangée 3033-DS-NICE - 3033-DS-NICE

<https://www.123roulement.com/roulement-palier/roulement-bille/simple-rangee/3033-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3033™			DS			+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.0005 -0.013
						0.6250 15.875	1.7000 44.450

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W ^⓪ (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)		d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5785	1025 4561	0.22 0.10	0.845 21.46	1.530 38.86	0.025 0.64

^⓪ Weights given are for greased and sealed versions
^⓪ 3033 and larger +.0000/-0.005 (-.000/-0.13)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558721
Diam. intérieur	15.875 mm
Diam. extérieur	44.45 mm
Épaisseur	12.7 mm
Poids	100 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE