

## Roulement à bille simple rangée 3035-SC-NICE - 3035-SC-NICE

<https://www.123roulement.com/roulement-palier/roulement-bille/simple-rangee/3035-sc-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3035™		SC				+0.005 +0.13 -0.000 -0.005	+0.000 +0.50 -0.005 -0.013
						0.7500 19.050	1.7500 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (lb) (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1025 4561	0.20 0.09	0.965 24.51	1.530 38.85	0.025 0.64

0 Weights given are for greased and sealed versions  
0 3035 and larger +.0000/-0.005 (+.000/-0.13)

### CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558769
Diam. intérieur	19.05 mm
Diam. extérieur	44.45 mm
Épaisseur	12.7 mm
Poids	90 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE