

Roulement à bille simple rangée
3040-NS-NICE - 3040-NS-NICE

https://www.123roulement.com/roulement-palier/roulement-bille/simple-rangee/3040-ns-nice

3000 Series® Semi-Ground Radial Bearings (con't)

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT RING
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX

BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN
3040™					NS

PRINCIPLE DIMENSIONS

BORE d (in) (mm)	O.D. D (in) (mm)
+0.005 +0.13 -0.000 -0.005	+0.000 +0.50 -0.013 -0.005
0.8750 22.225	2.0000 50.800

BASIC LOAD RATINGS

WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)
0.5625 14.288	1480 6588	1350 6008

WEIGHT

W (lb) (kg)
0.29 0.13

ABUTMENT AND FILLET DIMENSIONS

da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
1.113 28.27	1.760 44.70	0.035 0.89

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.0001/-0.0006 (+/-0.002/-0.015)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558899
Diam. intérieur	22.225 mm
Diam. extérieur	50.8 mm
Epaisseur	14.288 mm
Poids	130 g
Conditionnement	1

contact@123roulement.com
03 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE