


## Roulement à bille simple rangée 400-26V-NICE - 400-26V-NICE

<https://www.123roulement.com/roulement-palier/roulement-bille/simple-rangee/400-26v-nice>

**400** Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	26V	0.500 0.000 0.000	1.281 ±0.005/0.000 32.54	0.312 +0.010/-0.010 7.92	0.312 Reference 7.92	18	5/32 3.97

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.09 0.04	275 1224	193 859	133 592	107 478	75 334	52 231

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

### CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560090
Diam. intérieur	12.7 mm
Diam. intérieur	1/2" inch
Diam. extérieur	32.54 mm
Diam. extérieur	1 9/32" inch
Epaisseur	7.92 mm
Epaisseur	0.312" inch
Poids	40 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE