

Roulement à bille simple rangée 5507-V-NICE - 5507-V-NICE

<https://www.123roulement.com/roulement-palier/roulement-bille/simple-rangee/5507-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE		O.D.			WIDTH	
		A (in) (mm)	B (in) (mm)	C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5507™	V	0.312 +0.005/-0.000 +13/-00	1.125 +0.005/-0.000 +13/-00	0.365 +0.010/-0.010 +25/-25	0.062 9.78	1.250 31.75	0.125 3.18	0.437 11.10 +0.010/-0.010 +25/-25

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
		50 (lbs) (in)	100 (lbs) (in)	200 (lbs) (in)	300 (lbs) (in)	600 (lbs) (in)	1200 (lbs) (in)
NO.	SIZE	300	139	96	78	54	38
15	5/32 3.97	890	819	427	347	240	169

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560236
Diam. intérieur	7.92 mm
Diam. extérieur	28.58 mm
2nd Diam. extérieur	31.75 mm
Epaisseur	9.78 mm
2nd Epaisseur	11.1 mm
Poids	40 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE