

Roulement à bille simple rangée 5281-V-NICE - 5281-V-NICE

<https://www.123roulement.com/roulement-palier/roulement-bille/simple-rangee/5281-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE		O.D.		WIDTH		
		A (in) (mm)	B (in) (mm)	C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
		+0.005/-0.000 +13/-00	+0.005/-0.000 +13/-00	+0.010/-0.010 +25/-25				+0.010/-0.010 +25/-25
5281™	V	0.502 12.72	1.579 40.08	0.515 13.08	0.140 3.56	1.887 42.85	0.234 5.94	0.809 15.47

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
		50 (in) (%)	100 (in) (%)	200 (in) (%)	300 (in) (%)	600 (in) (%)	1200 (in) (%)
12	0.22 6.35	535 2381	367 1633	258 1148	206 917	144 641	100 445

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560298
Diam. intérieur	12.7 mm
Diam. extérieur	40.08 mm
2nd Diam. extérieur	42.85 mm
Epaisseur	13.08 mm
2nd Epaisseur	15.47 mm
Poids	100 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE