

Accessoire de palier 7608-DL-NICE - 7608-DL-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/7608-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE "H9/H8" STANDARD
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX. SPEED RANGE: 5000 - 8000 RPM
- THROUGH HARDENED
- HARDENED RINGS
- 90° AND 180° CASE STABILIZED
- FINISHED BEARING STRIPPERS
- EXCELLENT APPLICABLE ANGULAR CONTACT ANGLES
- AVAILABLE SINGLE BEARINGS OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHAFT AND HOUSING BORE TOLERANCE AS AN OPTION
- PREDESIGNED FOR APPLICATIONS WHERE EXTENSIVE WEIGHT REDUCTIONS AND SPECIAL BEARINGS ARE REQUIRED.

- WHEN ORDERING PLEASE INDICATE DESIGNATION AND STYLE LETTERS OF BEARING DESIRED (I.A., DL, OR DLG)
- TOLERANCE FOR 7613™ AND LARGER IS +0.0005/-0.0006 (+0.0005/-0.015)
- RADIUS R INDICATES THE MAXIMUM FILLET RADIUS IN HOUSING OR SHAFT WHICH BEARING WILL CLEAR
- WEIGHTS GIVEN ARE FOR GREASED AND SEALING VERSIONS

BEARING	PRINCIPLE DIMENSIONS						
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		A (in) (mm)	F (in) (mm)	G (in) (mm)
	+0.0008 +0.020 -0.0000 -0.001	+0.0000 +0.000 -0.0008 -0.015	+0.000 +0.000 -0.005 -0.13	+0.000 +0.000 -0.005 -0.13	0.0625 1.58	1.009 25.63	+0.005 +0.13 -0.005 -0.13
7608™	.5000 12.70	1.7900 45.40	0.6250 15.88	0.0625 1.58	1.009 25.63	0.138 3.46	

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	Dynamic C _d (N)	Static C _s (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.982 50.37	0.405 10.29	0.233 5.92	10-32	0.035 0.89	2096 11548	1025 4561	0.38 0.16

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473394
Diam. intérieur	12.7 mm
Diam. extérieur	25.63 mm
Épaisseur	15.88 mm
Poids	160 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE