

Accessoire de palier 7610-DL-NICE - 7610-DL-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/7610-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring NICE®

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE "H9" BEARING STANDARD
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHRINK BEARING
- EXCELLENT APPLICABLE ANGLE OF CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRANK. THIS WILL CHANGE TO AN OPTION.
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEAT AND VIBRATION ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7610™	.6250 15.88	1.7500 44.45	0.6250 15.88	0.0625 1.59	1.000 25.40	0.138 3.46

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (N) (lbf)	Static C _s (N) (lbf)	W (kg) (lb)
0.042 1.07	1.922 48.82	1.992 50.60	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4561	0.32 0.15

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473417
Diam. intérieur	15.88 mm
Diam. extérieur	25.63 mm
Épaisseur	15.88 mm
Poids	150 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE