

Accessoire de palier 7612-DL-NICE - 7612-DL-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/7612-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring **NICE®**

- PRECISION ENGINEERED FOR ALL CONTACT SURFACES THROUGH TO THE "FIN BEARING"
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- THERMALLY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE SEALED
- EXCELLENT APPLICABLE ANGLE OF CONTACT
- AVAILABLE SINGLE OR DOUBLE END OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHAFT FUR. OPTION. THIS WILL ENHANCE AS AN OPTION.
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEAT AND VIBRATION ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7612™	.7500 19.05	1.7920 44.95	0.6250 15.88	0.0625 1.58	1.000 25.40	0.136 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W G (kg)
0.042 1.07	1.922 48.82	1.982 50.00 27.74	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2996 11548	1029 4061	0.28 0.13

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7612™ and larger is +.0005-.0006 (+.0005-.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473431
Diam. intérieur	19.05 mm
Diam. extérieur	25.63 mm
Épaisseur	15.88 mm
Poids	130 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE