

Accessoire de palier 7614-DL-NICE - 7614-DL-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/7614-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE®**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 8000 RPM
- PRECISION MANUFACTURE
- STEEL BEARING
- WIPER CASE STANDARD
- STANDARD BEARING STANDARD
- SHARPLY ANGLED SINGLE LIP CONTACT SURFACES
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHARP EDGE SURFACE, WITH POOR DIMENSIONS AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE WEIGHT, SIZE, SPEED, AND NOISE ARE IMPORTANT FACTORS

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		A (in) (mm)	F (in) (mm)
7614	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.005 -0.13	0.0025 1.58	1.308 33.17	0.136 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28	0.039 0.99	2970 13217	1350 6098	0.43 0.20

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
② Tolerance for 7613™ and larger is +0.0001-0.0006 (+0.0001-0.015)
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473455
Diam. intérieur	22.23 mm
Diam. extérieur	33.17 mm
Epaisseur	15.88 mm
Poids	200 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE