


## Accessoire de palier 7620-DL-NICE - 7620-DL-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/7620-dl-nice>

**7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)** NICE

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 5000 - 8000 RPM
- PRECISION MANUFACTURE
- STEEL BEARING
- WATER WASH RESISTANT
- STANDARD BEARING
- HEAVY APPROXIMATE ANGULAR CONTACT
- AVAILABLE IN SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHARP EDGE DESIGN, WITH FILLET DIMENSIONS AS SHOWN
- RECOMMENDED FOR APPLICATIONS WHERE WEIGHT, SIZE, SPEED, AND RIGIDITY ARE CRITICAL



| BEARING | PRINCIPLE DIMENSIONS      |                           |                            |                 |                   |                   |                   |
|---------|---------------------------|---------------------------|----------------------------|-----------------|-------------------|-------------------|-------------------|
|         | BORE<br>d<br>(in)<br>(mm) | O.D.<br>D<br>(in)<br>(mm) | WIDTH<br>B<br>(in)<br>(mm) |                 | A<br>(in)<br>(mm) | F<br>(in)<br>(mm) | G<br>(in)<br>(mm) |
| 7620™   | 1.2500<br>31.75           | 2.5625<br>65.08           | 1.9000<br>48.27            | 1.9000<br>48.27 | 0.0625<br>1.59    | 1.672<br>42.47    | 0.190<br>4.83     |

| PRINCIPLE DIMENSIONS |                   |                   |                   |                   |                                      | BASIC LOAD RATINGS       |  | WEIGHT                                  |                   |
|----------------------|-------------------|-------------------|-------------------|-------------------|--------------------------------------|--------------------------|--|---|-------------------|
| H<br>(in)<br>(mm)    | J<br>(in)<br>(mm) | K<br>(in)<br>(mm) | L<br>(in)<br>(mm) | M<br>(in)<br>(mm) | N<br>2 set<br>screws<br>(in)<br>(mm) | Radius R<br>(in)<br>(mm) | Dynamic<br>C <sub>d</sub><br>(lb)<br>(N) | Static<br>C <sub>s</sub><br>(lb)<br>(N) | W<br>(lb)<br>(kg) |
| 0.065<br>1.65        | 2.768<br>70.25    | 1.417<br>35.98    | 1.417<br>35.98    | 0.605<br>15.37    | 0.261<br>6.63                        | 1/4-28<br>0.089<br>2.26  | 5360<br>23852                            | 2620<br>11659                           | 0.71<br>0.32      |

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)  
② Tolerance for 7613™ and larger is +.0000/-0.0006 (+.000/-0.015)  
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
④ Weights given are for greased and sealed versions  
All bearing designations listed herein are trademarks of RBC NICE® Bearings.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | NICE          |
| N° Ean13        | 3616060473509 |
| Diam. intérieur | 31.75 mm      |
| Diam. intérieur | 1 1/4" inch   |
| Diam. extérieur | 42.47 mm      |
| Diam. extérieur | 1.672" inch   |
| Epaisseur       | 19.05 mm      |
| Epaisseur       | 3/4" inch     |
| Poids           | 320 g         |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE