


Accessoire de palier ER10-NICE - ER10-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/er10-nice>

ER Series Precision Ground Radial Bearings with **NICE**
Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "NICE" BEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LUBRICATION GROOVES PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN REMOVED ENVIRONMENTS
- OPTIONAL LIP FORMING SEAL IS AVAILABLE
- LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO ROUNDED DIP POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK OXIDE FINISH PROVIDES ADDITIONAL RESISTANCE



PRINCIPLE DIMENSIONS														
BASIC BEARING NUMBER	SHAFT Ø	OD	WIDTH		C	D	E	F	G	H	J	K	M	RADIUS
	(in)	(in)	A (in)	B (in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
ER10	5/8	1.8504	1.732	1.352	1.318	1.654	1.754	1.654	3/64	3/64	3/64	3/16	5/8	0.040
	15.88	47	44	34.32	33.52	42.38	44.35	42.38	1.91	1.91	1.91	4.76	15.88	1.02

RADIAL CAPACITY											WEIGHT		
Ø	P	3-SET SCREWS	BASIC LOAD RATING C	STATIC LOAD RATING Co	50	150	300	500	1200	1500		2500	5000
(in)	(in)		(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(kg)
0.694	2 1/16	10-32	2890	1480	921	638	508	427	319	278	250	198	0.56
2.39	52.38		12527	6588	4098	2839	2252	1760	1420	1237	1113	891	0.25

ⓘ Shaft tolerance +.0002/-0.005 (+.002/-0.13) Ⓢ For low torque version add suffix "SPFR"

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560830
Diam. intérieur	15.88 mm
Diam. extérieur	28.18 mm
Épaisseur	15.88 mm
Poids	250 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE