

Accessoire de palier ER24-NICE - ER24-NICE

<https://www.123roulement.com/roulement-palier/paliers/accessoires/er24-nice>

ER Series Precision Ground Radial Bearings with **NICE**
Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "V" BEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL TRAILER GUARD AND INNER RING LUBRICATION GROOVES PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LOW-FRICTION SEAL IS AVAILABLE
- LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO SHARDED CUP POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK OXIDE FINISH PROVIDES ADDITIONAL RESISTANCE



PRINCIPLE DIMENSIONS														
BASIC BEARING NUMBER	SHAFT Ø	OD	WIDTH		C	D	E	F	G	H	J	K	M	RADIUS
	(in)	(in)	A (in)	B (in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
ER24	1 1/2	3.1496	1 15/16	3/4	1 3/16	29/32	2 3/64	1/4	1/16	1/8	5/16	1 3/32	0.062	
	38.10	80	39.23	19.05	35.16	23.02	11.98	6.35	1.59	3.18	7.64	27.78	1.57	

RADIAL CAPACITY										WEIGHT			
Ø	P	3-SET SCREWS	BASIC LOAD STATIC LOAD		REVOLUTIONS PER MINUTE						W		
			RATING C	RATING Co	50	150	300	500	1200	1800		2500	5000
(in)	(in)		(lbf)	(lbf)	(N)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(kg)
0.203	3 13/32	5/16-24	5535	4025	2103	1428	1157	976	729	637	571	453	2.00
3.15	80.50		25081	17911	3058	1918	1516	1343	1014	886	791	621	0.91

ⓘ Shaft tolerance +.0002/-0.005 (+.002/-0.13) Ⓢ For low torque version add suffix "SFF"

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560892
Diam. intérieur	38.1 mm
Diam. extérieur	51.99 mm
Épaisseur	27.78 mm
Poids	910 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE