


# Rotule TSM MXL-M08-6-DUNLOP - MXL-M08-6-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/tsm/mxl-m08-6-dunlop>

**MALE ROD ENDS** **DUNLOP**



**MALE ROD ENDS**

**MX SERIES**

**Description:**  
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: S17M 40, heat treated to 80/90 tons/m<sup>2</sup> tensile, Phosphated all over.  
Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available  
Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Forged S17M40, Heat Treated to 80/90 tons/m<sup>2</sup> tensile and Phosphated all over. **Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	D	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MXL-M08-R	MXL-M08-L	9.5	8.1	9.5	20.6	41.5	26	M8 x 1.25	22		11770

**Interchange table**

Dunlop	Rose	NMB
MX-M (metric)	RBJ-M	RBJ-M
MX (imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060550545
Diam. intérieur	6 mm
Diam. extérieur	9.5 mm
Épaisseur	8.1 mm
Type	TSM
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE