


Rotule PHS FP-M25-DUNLOP - FP-M25-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/phs/fp-m25-dunlop>

FEMALE ROD ENDS 



FEMALE ROD ENDS

FP SERIES: FP - FPS - FP SS

Description:
FP-Series is our 3-piece standard range of self-lubricating general purpose female rod ends, suitable for light to medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. They have excellent moisture resistance and require no maintenance and have a wide operating temperature range.

Material Specifications:
Housing: Steel 230M07PB and forged 980M44, zinc plated and clear trivalent passivate and stainless steel 303L 304. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated and stainless steel 440C and *SAE440. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303L.

Features:
Metric & imperial thread & bore sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance

Studded option

Possible Applications:
Light to medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles

Precision equipment
Linear movement

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Steel 230M07PB 1588p M12 - M121
Forged 980M44 Sizes M12 - M25
Zinc Plated and Clear Trivalent Passivate

Race: GR-Nylon LV-3H

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial [Newtons]
FP-M25		25	M24x2.00	31	22.00	60	14	48	29.40	36.0	67,140

Interchange table

Dunlop	Rose	Tuthill	Alinabal	IKO	SKF	Asahi
FP-M (metric)	MFP	FJ-M	MFF	PHS-EC	SIRB-F	JAF-EC
FP (imperial)	RFP-U	TJ	PF	PHSD-EC	-	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060551443
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	60 mm
Diam. extérieur	2.362" inch
Epaisseur	31 mm
Epaisseur	1.22" inch
Type	TSM
Filetage	Filetage à droite
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE