

## Rotule SI FP-16-DUNLOP - FP-16-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/si/fp-16-dunlop>

FEMALE ROD ENDS 



**FEMALE ROD ENDS**




**FP SERIES: FP - FPS - FP SS**

**Description:**  
FP-Series is our 3-piece standard range of self-lubricating general purpose female rod ends, suitable for light to medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. They have excellent moisture resistance and require no maintenance and have a wide operating temperature range.

**Material Specifications:**  
Housing: Steel 230M07PB and forged 980M44, zinc plated and clear trivalent passivate and stainless steel 303L 304. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated and stainless steel 440C and \*SAE440. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303L.

**Features:**  
Metric & imperial thread & bore sizes  
Low friction  
Self-lubricating  
Good wear resistance  
Excellent moisture resistance  
No maintenance

**Possible Applications:**  
Light to medium/heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles

**Temperature Range:**  
-30°C to +170°C

**Specification:**  
ELV & RoHS compliant

**Studded option**  
**Precision equipment**  
**Linear movement**

**Housing:** Steel 230M07PB (Stair 33 - 07)  
Forged 980M44 (Stair 05 114)  
Zinc Plated and Clear Trivalent Passivate

**Race:** GR-Nylon LV-3H

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
FP-16	1	1"	UNF	1,375	1,000	2,500	4,125	4,125	1,486	1,500	65,200

**Interchange table**

Dunlop	Rose	Tuthill	Alinabal	IKO	SKF	Asahi
FP-M (metric)	MFP	FJ-M	MFF	PHS-EC	SIRB-F	JAF-EC
FP (imperial)	RFP-U	TJ	PF	PHS-EC	-	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060552952
Diam. intérieur	25.4 mm
Diam. extérieur	63.5 mm
Epaisseur	34.925 mm
Type	SI
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE